



LANKO

401 SOLAR TAC



Waterproofing

ACRYLIC WATERPROOFING AND HEAT PREVENTION



CHARACTERISTICS

- Reduce interior temperature of building.
- Mould resistant.
- Energy saving.
- Flexible.
- Solvent free.
- Easy to use.
- Color available Grey, white, red, brown, green or blue.

DESCRIPTION

An acrylic waterproofing and and heat reflectant. It minimise temperature by reducing the heat.

USES

- Main use : roof and wall.
- Exterior.
- Substrates: concrete, render, metal, cement sheet, masonry, brick.

WORK INSTRUCTIONS

Surface Preparation

1. Surface must be clean and without any trace of oil.

Product preparation

1. Apply directly from the bucket.
2. Pre-stir prior to application.

Application

1. Adhesion to porous concrete can be improved by using LANKO 461 ACRYLIC PRIMER.
2. Apply 1st coat with brush, roller or spray. Allow 2-4 hours of drying time so that it is not drawn off while applying the 2nd coat.
3. Apply 2nd coat, crosswise.



UV Resistant



Roof



Wall



Paintable



High Flexible



Color

PACKAGING

- 20 kg. bucket.

STORAGE

- 1 year from date of manufacture if stored in unopened original packaging in dry condition.



PRECAUTIONS

- Temperature range for use : 5°C to 35°C.
- Do not apply in full sunlight.

SPECIFICATIONS

Appearance	: Paste
Paste density (kg./L)	: 1.14-1.15
Elongation (%)	: > 500%
Heat reflectance (%)	: > 99%
Shore hardness	: 60-70

Water absorption (%)	Evaluation
30 min.	0%
240 min.	0%

Adhesion to concrete ASTM D4515 (Mpa)	Evaluation
28 days	> 1

Sika (Thailand) Limited

700/ 37 Moo 5, Amata City Chonburi Industrial Estate, Km.57 Bangna-Trad Rd, Klong Tamhru, Muang, Chonburi 20000

*The information provided in this document results from our knowledge of the products and our experience. On-site results may vary, in particular according to the product application methods adopted. Where application methods not representative test before using the products. The above-mentioned information in no way constitutes a warranty relative to the use of the products. Our general terms and conditions of sale shall prevail, in any event, on the information provided in this document. Prior to application, customers and users are requested to check that they have the latest version of this document.



e-learning VDO